

RX series

- 19mm Mylar Balanced Dome Tweeter
- 12dB External Audiophile Crossover (RX65cs)
- Integrated Phase Plug (RX65cs)
- Anti-Resonant Steel Basket
- High Temperature CAE/CAD Motor Structure

- Triple Laminated, Ultra Stiff and Light Cone
- UV Treated Foam Surround



	<i>RX65cs</i>	<i>RX69cx</i>	<i>RX5cx</i>	<i>RX65cx</i>	<i>RX46cx</i>	<i>RX57cx</i>	<i>RX4cx</i>
Size	6.5"	6" x 9"	5.25"	6.5"	4" x 6"	5" X 7"	4"
Power Handling	125w RMS - 250w PEAK	60w RMS - 120w PEAK	40w RMS - 80w PEAK	50w RMS - 100w PEAK	40w RMS - 80w PEAK	50w RMS - 100w PEAK	40w RMS - 80w PEAK
Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Frequency Response	60Hz to 20kHz	70Hz to 20kHz	70Hz to 20kHz	70Hz to 20kHz	70Hz to 20kHz	70Hz to 20kHz	70Hz to 20kHz
Mounting Depth	2.5" - 64mm	3" - 76mm	2.2" - 55mm	2.5" - 64mm	2.1" - 51.5mm	2.8" - 71mm	2" - 50mm
Cut Out Diameter	5.7" - 144mm	8.7" x 6.1" - 221mm x 154mm	4.75" - 120mm	5.7" - 144mm	5.6" x 3.5" - 143mm x 88mm	7.4" x 5.2"-188mm x 131mm	3.7" - 93mm