

SX series

- 20mm Silk Dome Tweeter
- Tweeter Flush Mount or Surface Mount Capability (SX65cs, SX5cs)
- Adjustable Tweeter Swivel Mount (SX65cs, SX5cs)
- Tweeter Level Adjustment (SX65cs, SX5cs)
- 24dB External Audiophile Crossover (SX65cs, SX5cs)
- Integrated Phase Plug (SX65cs, SX5cs)

- Aluminum Plated Grained Polypropylene Cone
- Powdercoated Anti-Resonant Steel Basket
- Interwoven Tinsel Leads
- Butyl Rubber Surround
- High Temperature CAE/CAD Motor Structure
- Optimized Magnet/Motor Structure



	SX65cs	SX5cs	SX69cx	SX65cx	SX57cx	SX6cx	SX5cx
Size	6.5"	5.25"	6" x 9"	6.5"	5" x 7"	6"	5.25"
Power Handling	125w RMS - 250w PEAK	125w RMS - 250w PEAK	90w RMS - 180w PEAK	75w RMS - 150w PEAK	75w RMS - 150w PEAK	75w RMS - 150w PEAK	60w RMS - 120w PEAK
Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Frequency Response	60Hz to 20kHz	60Hz to 20kHz	50Hz to 20kHz	60Hz to 20kHz	60Hz to 20kHz	60Hz to 20kHz	70Hz to 20kHz
Mounting Depth	2.9" - 73mm	2.4" - 61mm	3.3" - 83mm	2.9" - 73mm	2.6" - 65mm	2.6" - 65mm	2.4" - 61mm
Cut Out Diameter	5.6" - 145mm	4.5" - 118mm	8.6" x 6.1" - 154mm x 222mm	5.6" - 145mm	7.2" x 5" - 129mm x 183mm	4.9" - 131mm	4.5" - 118mm