



- 24dB External Audiophile Grade Crossover (Ti265CS)
- Three Position Tweeter Level Adjustment (Ti265CS)
- Midbass Enhancement EQ Adjustment (Ti265CS)
- 20mm Silk Dome Tweeter w/ Removable Aluminum Housing (Ti265CS)
- Continuous Play Tweeter Protection Circuitry
- Precision Cone Control Dual Roll Rubber Surround
- High Temperature CAE/CAD Motor Structure
- Pointsource Tweeter and Midrange Design (Ti265ps, Ti257ps, Ti269ps)
- Poly Treated Paper Cone
- Interwoven Tinsel Leads
- Powdercoated Anti-Resonant Steel Basket



	Ti265cs	Ti269ps	Ti257ps	Ti265ps
Size	6.5"	6" x 9"	5" x 7"	6.5"
Power Handling	125w RMS - 250w PEAK	100w RMS - 200w PEAK	100w RMS - 200w PEAK	100w RMS - 200w PEAK
Impedance	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Frequency Response	50Hz to 20kHz	50Hz to 20kHz	50Hz to 20kHz	50Hz to 20kHz
Mounting Depth	2.46" - 62.5mm	3.1" - 78mm	2.4" - 59mm	2.55" - 65mm
Cut Out Diameter	5.57" - 141.5mm	6" x 8.7" - 151mm x 221mm	5" x 7.2" - 127mm x 182mm	5.7" - 145mm